MICROTEX

FR2P - FASTREADER 2

ANSI TYPE 2 56K Zero Power Optical Probe



SPECIFICATIONS:

HEAD Indestructable Polycarbonate

CABLE Superflex PV Cable & Strain Relief

CONNECTOR Compatible with All Host Connectors

LENS Built-IN Polycarbonate Filter

OPTICAL 880nm IR bidirectional Optical Link

DOCKING Magnetic Adhesion – 6 Magnet

POWER Power derived from host port < 10mA.

SIGNAL EIA232D, V28, V32, TTL

MAX DATA 57,600 bits/second

OPERATING -30c to +75c Temperature Range

Standards Mil Std 810E & 801-3, IEC801-2 ESD

Compatibility Compatible with any Electric Utility Meter

supporting the ANSI C12.18 Standard

protocol.

- ✓ ANSI C12.18 (1996) Standard
- ✓ Sunlight Filter
- ✓ Rugged Aluminum Head
- ✓ Flexible High-Endurance Coiled Cord
- √ Strain Relief / Sealed Head
- ✓ RS232 & EIA232D operation
- ✓ Zero-Power Operation

MICROTEX ANSI TYPE 2 "FAST READER"

The Microtex Electronics FR2P ANSI Type 2
"Fast Reader" is the LOW-COST solution for reading electric utility meters with portable handhelds Made by ITRON, DAP Technologies, Radix, Corvallis, PSION, and PC Laptops. The zero-power interface derives power completely from the handheld computer's host port interface. This saves the user from having to supply battery packs or provide for a "dongle cable" This product features an indestructible polycarbonate head, and tough Hytrel™ coiled cord connections to laptop or PC computer terminals. This unit supports the bidirectional IR interface for terminal speeds up to 57,600 bits per second.

READS these Meters:

ABB - All Alpha, Alpha+, A3, ION-8400, ION-

8500 compatible

Ametek/Scientific Columbus – JEM-1, JEM-10, Jemstar compatible

Power Measurements – ION 7000, 8000 series

Quadlogic – Series 20 compatible

Itron - Q1000, Quantum Q121, Sentinel,

Centron, Vectron and compatible.

GE - KV, GE-KV2, KV2-C

Landis&Gyr – S4 Family, AXS4, AXRS4, AXLS4, RXS4, RXRS4, MAXSYS family, MAXSYS 2410, MAXSYS 2510, Quad 4

Transdata - Mark V

ORDERING INFORMATION on Back:

For More Information:

Microtex Electronics, INC. 2929 N. Central Expressway, Suite 250 Richardson, TX 75080 U.S.A www.microtexelectronics.com TEL: (972) 479-1011 FAX: (972) 479-1015



MICROTEX

FR2P - FASTREADER 2

Ordering Information



FR2P - PC - XX (xx=length)

Supports all Laptops, Portables, and Personal Computers. Connector is a DB9 female. Derives power from the RS232 port so no Battery packs or "Dongle" power cables are required. Superflex straight cable comes in *6', 10', 15', 25', 50' and 100' straight cable lengths.

* = Standard cord length



FR2 - USB - XX (xx=length)

Supports all Handhelds and laptops. USB unit comes with Windows 98/ME/2000/XP Com port simulator driver. Superflex straight USB cable comes in *6', 10' or 15' straight cable lengths. * note due to limitations of the USB 2.0 specification, cables longer than 15 feet are non available.

* = Standard cord length

MICROTEX ELECTRONICS OFFERS A ONE-YEAR LIMITED WARRANTY ON ANY FASTREADER PRODUCT. WE ALSO OFFER MAINTENANCE PLANS AND SERVICE WHAT WE BUILD.

For More Information:

Microtex Electronics, INC. 2929 N. Central Expressway, Suite 250 Richardson, TX 75081 U.S.A www.microtexelectronics.com TEL: (972) 479-1011

TEL: (972) 479-1011 FAX: (972) 479-1015 **Proudly Made in the USA**

