



MICROTEX ELECTRONICS, INC.

FR2 - FASTREADER 2

ANSI TYPE 2 56K Zero Power Optical Probe



SPECIFICATIONS:

HEAD	Indestructible T6016 Aluminum
CABLE	Superflex PV Cable & Strain Relief
CONNECTOR	Compatible with All Host Connectors
LENS	IR Polycarbonate Filter
OPTICAL	880nm IR bidirectional Optical Link
DOCKING	Magnetic Adhesion – 6 Magnet
POWER	Power derived from host port < 10mA.
SIGNAL	EIA232D, V28, V32, TTL
MAX DATA	57,600 bits/second
OPERATING	-30c to +75c Temperature Range
Standards	Mil Std 810E & 801-3, IEC801-2 ESD
Compatibility	Compatible with any Electric Utility Meter supporting the ANSI C12.18 Standard protocol.

- ✓ ANSI C12.18 (1996) Standard
- ✓ Sunlight Filter
- ✓ Rugged Aluminum Head
- ✓ Flexible High-Endurance Coiled Cord
- ✓ Strain Relief / Sealed Head
- ✓ RS232 & EIA232D operation
- ✓ Zero-Power Operation

MICROTEX ANSI TYPE 2 “FAST READER”

The **Microtex Electronics FR2 ANSI Type 2 “Fast Reader”** is the **LOW-COST** solution for reading electric utility meters with portable handhelds Made by ITRON, DAP Technologies, Radix, Corvallis, PSION, and PC Laptops. **The zero-power interface derives power completely from the handheld computer’s host port interface.** This saves the user from having to supply battery packs or provide for a “dongle cable” This product features an indestructible head, and tough Hytrel™ coiled cord connections to laptop or PC computer terminals. This unit supports the bi-directional IR interface for terminal speeds up to 57,600 bits per second.

READS these Meters and more:

- ABB** – All Alpha, Alpha+, A3, ION-8400, ION-8500 compatible
- Ametek/Scientific Columbus** – JEM-1, JEM-10, Jemstar compatible
- Power Measurements** – ION 7000, 8000 series
- Quadlogic** – Series 20 compatible
- Itron** – Q1000, Quantum Q121, Sentinel, Centron, Vectron and compatible.
- GE** - KV, GE-KV2, KV2-C
- Landis&Gyr** – S4 Family, AXS4, AXRS4, AXLS4, RXS4, RXRS4, MAXSYS family, MAXSYS 2410, MAXSYS 2510, Quad 4
- Transdata** – Mark V

ORDERING INFORMATION on Back:

For More Information:

Microtex Electronics, INC.
 3400 North Central Expressway, Ste 256
 Richardson, TX 75080 U.S.A
 www.microtexelectronics.com
 TEL: (972) 479-1011
 FAX: (972) 479-1015

Proudly Made in the USA





MICROTEX ELECTRONICS, INC.

FR2 - FASTREADER 2

Ordering Information



FR2 - PC - XX (xx=size) (add -E for European)

Supports all Laptops, Portables, and Personal Computers. Connector is a DB9 female. Derives power from the RS232 port so No Battery packs or "Dongle" power cables are required. Superflex cable expands 5 times its length. Sizes are *18" (standard), 36", 48", and 64"



FR2 - DAP - XX (xx=size) (add -E for European)

Supports all Handhelds manufactured by DAP technologies. Connector to handheld is a Right angle LEMO connector. Tested on models DAP9500, DAP9800, CE5240, and CE 5320. Superflex cable expands 5 times its length. Sizes are *18' (standard), 36", 48", and 64"



FR2- FS -XX (xx=size) (add -E for European)

Supports handhelds manufactured by ITRON Technologies. Connector is Amphenol type. Tested on ITRON models FS2, and FS3. Superflex cable expands 5 times its length. Sizes are *18' (standard), 36", 48", and 64"



FR2 - G5 - XX (xx=size) (add -E for European)

Supports handhelds manufactured by ITRON technologies. Connector is G5 type. Tested on ITRON model G5. Superflex cable expands 5 times its length. Sizes are *18' (standard), 36", 48", and 64"

MICROTEX ELECTRONICS OFFERS A ONE-YEAR LIMITED WARRANTY ON ANY FASTREADER PRODUCT. WE ALSO OFFER MAINTENANCE PLANS AND SERVICE WHAT WE BUILD.

For More Information:

Microtex Electronics, INC.
3400 North Central Expressway, Ste 256
Richardson, TX 75080 U.S.A
www.microtexelectronics.com
TEL: (972) 479-1011
FAX: (972) 479-1015

Proudly Made in the USA



©2002 Microtex Electronics, Inc.. All information, specifications, and descriptions contained herein are subject to change without prior notice.